

YOUR SAFE ENERGY

15-year Design Lifespan

A+ Grade Lithium Iron Phosphate Cells

Model: Flex16-n(n=3,4...6)

Model: Flex16-n(n=7,8...16)

Active Balancing Technology

Indoor installation

Smart Air-Cooled Battery

430 VDC Version (3–6 Battery Packs)

Energy Capacity: 48–96 kWh

Battery Voltage: 134.4–350.4 V

1000 VDC Version (7–16 Battery Packs)

Energy Capacity: 112–257 kWh

Battery Voltage: 313.6–934.4 V



Features and Advantages

Safety Technology

- Grade A+ lithium iron phosphate cells
- The system features multi-level fuse protection
- Built-in aerosol fire suppression device at pack level

Flexible and Expandable

- Supports up to 12 clusters in parallel
- 48kWh~3086kWh capacity

Module Mixing

- Modules manufactured within one year can be mixed

Easy to Install and Use

- Modules use a wireless stacking connection
- Ergonomic handles provide a secure grip and better balance for lifting and manual handling

Compatible inverters

- Solis, iNVT, Fox ESS, Solinteg and Growatt

Scheme 1: System Technical Parameters – 430 VDC Version (3–6 Battery Packs)

Model		Flex16-3	Flex16-4	Flex16-5	Flex16-6
Battery Data					
Number of battery packs		3	4	5	6
Nominal Energy		48.23kWh	64.30kWh	80.38kWh	96.46kWh
Nominal Voltage		153.6V	204.8V	256V	307.2V
Battery Model		Flex16-Unit			
Battery Chemistry		Lithium Iron Phosphate(LiFePO4)			
Cycle Life[1]		≥8000 cycles			
Cell Specification		3.2V 314Ah			
Battery Pack Energy		16.076 kWh			
Number of Clusters		1			
Cluster Configuration		1P48S	1P64S	1P80S	1P96S
Operating Voltage		134.4V - 175.2V	179.2V - 233.6V	224V - 292V	268.8V - 350.4V
Recommended Charge/Discharge C-rate		0.5C (157A)			
Maximum Charge/Discharge C-rate		0.64C (200A)			
Peak Discharge Current (25°C)		280A			
Recommended Charge/Discharge Power		8.038 kW			
Maximum Charge/Discharge Power		10.24 kW			
Depth of Discharge (DOD)		95%			
Cell Balancing Technology		Active balancing			
Installation		Cableless stacking			
Scalability		up to 12 clusters in parallel			
Safety					
Fire Extinguishing System		Integrated aerosol fire suppression device			
General					
Dimension(WxDxH) mm	1 Column	830 x 490 x 1120	830 x 490 x 1350	830 x 490 x 1580	830 x 490 x 1810
	2 Columns	/	/	/	/
Weight		Approx. 407kg	Approx. 524kg	Approx. 641kg	Approx. 770kg
IP Rating		IP20			
Cooling Method		Smart air cooling			
Charging Temperature		0°C to +55°C			
Discharging Temperature		-20°C to +55°C			
Storage Temperature		-20°C to +45°C			
Relative Humidity		15%~90%(Non-condensing)			
Max. Operating Altitude		≤2000m			
Communication Interfaces		LAN/CAN/RS485/Wi-Fi			
Compliance		UN 38.3, MSDS			

* The actual product may have slight differences from some promotional videos or pictures. Please refer to the actual product. Unless otherwise specified, the data on this page are all from our company's laboratory. The data may have errors due to changes in the objective environment.

* The specifications are subject to change without prior notice.

[1]Test Conditions: Charge/discharge at 0.2C, 25°C, 95% depth of discharge (DOD), 70% end-of-life (EOL)

Scheme 2: System Technical Parameters – 1000 VDC Version (7–11 Battery Packs)

Model	Flex16-7	Flex16-8	Flex16-9	Flex16-10	Flex16-11
Battery Data					
Number of battery packs	7	8	9	10	11
Nominal Energy	112.53kWh	128.61kWh	144.69kWh	160.76kWh	176.84kWh
Nominal Voltage	358.4V	409.6V	460.8V	512V	563.2V
Battery Model	Flex16-Unit				
Battery Chemistry	Lithium Iron Phosphate(LiFePO4)				
Cycle Life[1]	≥8000 cycles				
Cell Specification	3.2V 314Ah				
Battery Pack Energy	16.076 kWh				
Number of Clusters	1				
Cluster Configuration	1P112S	1P128S	1P144S	1P160S	1P176S
Operating Voltage	313.6V - 408.8V	358.4V - 467.2V	403.2V - 525.6V	448V - 584V	492.8V - 642.2V
Recommended Charge/Discharge C-rate	0.5C (157A)				
Maximum Charge/Discharge C-rate	0.64C (200A)				
Peak Discharge Current (25°C)	280A				
Recommended Charge/Discharge Power	8.038 kW				
Maximum Charge/Discharge Power	10.24 kW				
Depth of Discharge (DOD)	95%				
Cell Balancing Technology	Active balancing				
Installation	Cableless stacking				
Scalability	up to 12 clusters in parallel				
Safety					
Fire Extinguishing System	Integrated aerosol fire suppression device				
General					
Dimension(WxDxH) mm	1 Column	/	/	/	/
	2 Columns	2110 x 490 x 1170	2110 x 490 x 1300	2110 x 490 x 1400	2110 x 490 x 1530
Weight	Approx. 910kg	Approx. 1030kg	Approx. 1150kg	Approx. 1270kg	Approx. 1390kg
IP Rating	IP20				
Cooling Method	Smart air cooling				
Charging Temperature	0°C to +55°C				
Discharging Temperature	-20°C to +55°C				
Storage Temperature	-20°C to +45°C				
Relative Humidity	15%~90%(Non-condensing)				
Max. Operating Altitude	≤2000m				
Communication Interfaces	LAN/CAN/RS485/Wi-Fi				
Compliance	UN 38.3, MSDS				

* The actual product may have slight differences from some promotional videos or pictures. Please refer to the actual product. Unless otherwise specified, the data on this page are all from our company's laboratory. The data may have errors due to changes in the objective environment.
 * The specifications are subject to change without prior notice.

[1]Test Conditions: Charge/discharge at 0.2C, 25°C, 95% depth of discharge (DOD), 70% end-of-life (EOL)

Scheme 2: System Technical Parameters – 1000 VDC Version (12–16 Battery Packs)

Model	Flex16-12	Flex16-13	Flex16-14	Flex16-15	Flex16-16
Battery Data					
Number of battery packs	12	13	14	15	16
Nominal Energy	192.92kWh	208.99kWh	225.07kWh	241.15kWh	257.22kWh
Nominal Voltage	614.4V	665.6V	716.8V	768V	819.2V
Battery Model	Flex16-Unit				
Battery Chemistry	Lithium Iron Phosphate(LiFePO4)				
Cycle Life[1]	≥8000 cycles				
Cell Specification	3.2V 314Ah				
Battery Pack Energy	16.076 kWh				
Number of Clusters	1				
Cluster Configuration	1P192S	1P208S	1P224S	1P240S	1P256S
Operating Voltage	537.6V - 700.8V	582.4V - 759.2V	627.2V - 817.6V	672V - 876V	716.8V - 934.4V
Recommended Charge/Discharge C-rate	0.5C (157A)				
Maximum Charge/Discharge C-rate	0.64C (200A)				
Peak Discharge Current (25°C)	280A				
Recommended Charge/Discharge Power	8.038 kW				
Maximum Charge/Discharge Power	10.24 kW				
Depth of Discharge (DOD)	95%				
Cell Balancing Technology	Active balancing				
Installation	Cableless stacking				
Scalability	up to 12 clusters in parallel (3086kWh)				
Safety					
Fire Extinguishing System	Integrated aerosol fire suppression device				
General					
Dimension(WxDxH) mm	2 Columns	/	/	/	/
	3 Columns	2560 x 490 x 1300	2560x 490 x 1400	3390 x 490 x 1530	3390 x 490 x 1530
Weight	Approx. 1530kg	Approx. 1650kg	Approx. 1770kg	Approx. 1890kg	Approx. 2010kg
IP Rating	IP20				
Cooling Method	Smart air cooling				
Charging Temperature	0°C to +55°C				
Discharging Temperature	-20°C to +55°C				
Storage Temperature	-20°C to +45°C				
Relative Humidity	15%~90%(Non-condensing)				
Max. Operating Altitude	≤2000m				
Communication Interfaces	LAN/CAN/RS485/Wi-Fi				
Compliance	UN 38.3, MSDS				


* The actual product may have slight differences from some promotional videos or pictures. Please refer to the actual product. Unless otherwise specified, the data on this page are all from our company's laboratory. The data may have errors due to changes in the objective environment.
 * The specifications are subject to change without prior notice.

[1]Test Conditions: Charge/discharge at 0.2C, 25°C, 95% depth of discharge (DOD), 70% end-of-life (EOL)

Features and Advantages

- The product supports manual control and shunt trip control of the DC circuit breaker
- Built with high-reliability components and redundant protection design, the product withstands EMI, high temperature, and vibration ensuring high reliability and stability
- The front panel features operating status indicators for easy identification
- It supports temperature monitoring of busbars and power connectors in the high-voltage box to ensure system safety
- It provides accurate monitoring of battery cluster voltage, current, and insulation resistance status

Dimensions(WxDxH mm)




High Voltage Box Technical Parameters

Model	Flex16-HBox
Rated Voltage	1000 VDC (430 VDC optional)
Rated Current	250A
Insulation Resistance	$\geq 10 \text{ M}\Omega$ at 1000 VDC (430 VDC optional)
Dielectric Strength	3390 VDC, leakage current $\leq 1 \text{ mA}$, no breakdown or flashover
Operating Temperature	-20°C to +65°C
Storage Temperature	-25°C to +65°C
Relative Humidity	$\leq 95\%$
Cooling Method	Natural convection
Altitude	$\leq 2000 \text{ m}$
Dimensions (WxDxH mm)	830x490x230 mm
Weight	40 kg
Communication	CAN/RS485/LAN
Ingress Protection	IP20

*Note: Two high-voltage box versions are available: 430 VDC and 1000 VDC.
 *Please specify the required version when placing the order.

Dimensions(WxDxH mm)



Battery Pack Technical Parameters

Model	Flex16-Unit
Nominal Energy	16.076 kWh
Nominal Voltage	51.2 V
Rated Capacity	314 Ah
Battery Balancing	Active balancing
Balancing Current	up to 2A
Recommended Charge/Discharge C-rate	0.5C (157A)
Maximum Charge/Discharge C-rate	0.64C (200A)
Peak Discharge Current (25°C)	280A
Recommended Charge/Discharge Power	8.038 kW
Maximum Charge/Discharge Power	10.24 kW
Charging Temperature	0°C to +55°C
Discharging Temperature	-20°C to +55°C
Storage Temperature	-20°C to +45°C
Dimensions(W x D x H mm)	830 x 490 x 230 mm
Battery Weight (Approx.)	117 Kg